

University of Illinois Department of Agricultural and Biological Engineering
 Bioenvironmental and Structural Systems Lab
 Final Report

Project Number: 21082
 Test Date: February 5, 2021

Fan:		Motor:		Shutter:	Butterfly damper
Make- <i>Chore-Time</i>		Make- <i>Marathon</i>		Material- <i>Poly</i>	
Model- <i>54659-22</i>		Model- <i>K56AD40C58</i>		# Doors- <i>2</i>	
Blade dia.- <i>56.8"</i>		Hp- <i>1.5</i>		# Columns- <i>-</i>	
Orifice dia.- <i>57.3"</i>		RPM- <i>1725</i>		Door length- <i>-</i>	
		Volts- <i>230</i>		Location- <i>exhaust</i>	
Blade:		Amps <i>6</i>			
Number- <i>3</i>		Hz- <i>60</i>		Guards:	
Shape- <i>propeller</i>		Phase- <i>1</i>		Description- <i>wire</i>	
Material- <i>galvanized steel</i>		S. F.- <i>1.2</i>		Spacing- <i>2" x 4" / 5.5" concentric</i>	
Pitch- <i>-</i>				Location- <i>intake / exhaust</i>	
Clearance- <i>0.2"</i>		Housing:		Discharge Cone:	
		Material- <i>Poly</i>		Depth- <i>34.8"</i>	
Drive Sheaves:		Intake area- <i>59" dia.</i>		Minor dia.- <i>56.6"</i>	
Drive dia.- <i>3.05" o.d.</i>		Discharge- <i>56.6"</i>		Major dia.- <i>70"</i>	
Axle dia.- <i>9.8" o.d.</i>		Depth- <i>10.5" + 21.2" housing</i>			

Notes: 0

Test Conditions:

T(wb): 52.5	Barometric pressure, recorded	29.10
T(db): 75	Barometric Pressure, corrected	28.98

							SI Units			
Static Pressure	Airflow						Static Pressure	Airflow		
(in.H2O)	(cfm)	rpm	Volts	Amps	Watts	cfm/Watt	(Pa)	(m^3/hr.)	(m^3/hr)/W	W/1000m^3/hr
0.00	29800	544	229.8	5.01	1094	27.2	0	50600	46.2	22
0.05	28100	543	229.9	5.30	1169	24.1	12	47800	40.9	24
0.10	26200	541	229.7	5.56	1240	21.2	25	44600	36	28
0.15	24200	540	229.3	5.85	1312	18.4	37	41000	31.3	32
0.20	21800	539	229.9	6.10	1377	15.8	50	37100	26.9	37
0.25	18900	538	230.1	6.25	1415	13.3	62	32000	22.6	44
0.30	14200	537	229.9	6.37	1444	9.8	75	24100	16.7	60